

FD13BT



Freezer-Depth 70cm-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, for grilles 55x53cm. 2 doors. Temperature ranges: -20/-10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



Refrigeration power at -30°C W	750
--------------------------------	-----

General information

Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD13BT
Category	vertical cabinet
Type	freezer
Line	catering

Technical features

Temperature ranges, °C	-20/-10
Energy Efficiency Class	G
Energy consumption, kWh/24h	16,6
Energy consumption/year, kWh/a	6059
Method for energy consumption	EN 22041
Energy Efficiency Index	99,58
Net usable volume, lt	1020
Volume, gross, lt	1020
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,14
LWA dB(A)	67

Freezer-Depth 70cm-AISI 304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 31/07/2022 13.10.55



FD13BT



Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,92

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel)
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	24 plastic - coated hooks
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x55
Shelf loading capacity, kg	30

Dimensions and weights

Packing (LxDxH), cm	154x75x207
Dimensions (LxDxH), cm	150x70x204
Gross Weight (kg)	200
Net Weight (kg)	185

Freezer-Depth 70cm-AISI 304-Freezy Prime

