



Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-23 E

DIMENSIONS

		Article	Packed
Length	mm	890,00	960,00
Depth	mm	1.345,00	1.430,00
Height	mm	1.812,00	1.930,00
Weigth	Kg	338,00	370,00
Volumen	m3		2,64

ELECTRICITY

<u>Electric power</u>	KW		24,67
230V -1+N			NO
230V - III		3x25+T-125 A	
400V - III+N		4x10+T - 63 A	

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

TUMBLE DRYER, SR-23 E GREEN EVOLUTION

Load Capacity : 25 kg. (load factor 1:18) or 21 kg (load factor 1:22).
Production: + 46 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Time selector.

Temperature selector.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 1500 m3/h.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum .

Drum diameter: 855 mm

Depth of drum: 905 mm

Diameter of door: 574 mm.

reversible door hanging.

Fluff filter in lower part .

Transmission by means of motoreducer .

Main heating system: electric

Electrical connection : 400 V - III+N - 50/60 Hz.

Heating power: 24 kW

Total power: 24,67 kW.

Dimensions: 890 x 1.245 x 1.812 mm

OPTIONS:

- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	637	0	861		0
EXHAUST	663	0	174	200 mm.	

