

KUC2A



Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat.



General information

Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUC2A
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	3,918
Energy consumption/year, kWh/a	1430
Method for energy consumption	EN 22041
Energy Efficiency Index	56,05
Net usable volume, lt	298
Volume, gross, lt	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-AISI 304-Universal

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 29/07/2022 17.45.31



KUC2A



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	560
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,32

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	doors and drawers
Drawers, type: 1/2	2

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packing (LxDxH), cm	235,5x75,5x100
Dimensions (LxDxH), cm	230x70x98,5
Gross Weight (kg)	187
Net Weight (kg)	172

Refrigerated counter-GN1/1-AISI 304-Universal

