

KIBBM



Freezer counter-GN1/1-AISI 304-Idea

One-piece AISI 304 stainless steel body. Temperature ranges: -24/-12°C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1.3 doors. Control panel with digital thermometer - thermostat and communication port. Automatic defrost with hot gas and automatic evaporation of condense drain.



General information

Supplier/producer 's name	SAGI
Series	Idea
Supplier's model identifier	KIBBM
Category	counter cabinet
Type	freezer counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	-24/-12
Energy Efficiency Class	F
Energy consumption, kWh/24h	9,24
Energy consumption/year, kWh/a	3371
Method for energy consumption	EN 22041
Energy Efficiency Index	89
Net usable volume, lt	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	59
Cooling system	ventilated refrigeration system
Defrosting	automatic by hot gas
Evaporation of condense drain	automatic

Freezer counter-GN1/1-AISI 304-Idea

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 21/07/2022 13.38.33



Refrigeration power -23,3°C W	899
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	3 doors

Control and functions

Kind of control	digital thermometer/thermostat and communication port
Display	digital

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packing (LxDxH), cm	192x76x90
Dimensions (LxDxH), cm	185x70x90
Gross Weight (kg)	161
Net Weight (kg)	149