

TI32 R



- Heavy duty Professional equipment
- Structured in AISI 304 stainless steel
- Hermetic steel Oil immersed reducer
- Ventilated asynchronous motor
- Thermal protection included
- Easy-removable enterprise mouth unit available in: AISI 304 stainless steel
- Stainless steel self-sharpening draw-plates included
- Stainless steel tray and hopper
- ABS pestle
- Central control system requires 24 volt low tension
- On/off switch protection with waterproof rubber cover
- Optional cooling fan available for mod 32
- Gear inversion option included
- Sausage filling kit available on demand
- CE approved
- Proudly Made in Italy

TECHNICAL SHEET

| | |
|---|----------------------|
| Power (Kwatt/Hp) | 2,20 (3,00) |
| Power supply (Volt/Hz) | 230/50 - 230-400/50 |
| Screw revolution (RPM) | 140 |
| Production per hour (kg) | 600 |
| Barrel (mm) | ø98 |
| Inlet (mm) | ø52 |
| Standard plate (mm) | ø6 |
| Mincing Groups | inox |
| Net weight single/three phase (kg) | 52,0/46,0 |
| Gross weight single/three phase (kg) | 55,0/49,0 |
| Dimensions (mm) | B. 300 D. 475 H. 560 |
| Packaging dimensions (mm) | B. 430 D. 620 H. 650 |