



# VACUUM SEALER SU-520CC

Tabletop model. 20 m<sup>3</sup>/h. 420+420 mm.



FOOD PRESERVATION AND SOUS-VIDE  
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



## SALES DESCRIPTION

Two sealing bars ( 420+420 mm).  
20 m<sup>3</sup>/h Busch vacuum pump.  
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Long-shaped, deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

## INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

## OPTIONAL

- Inert gas
- Sealing plus
- Printer
- Bluetooth connectivity
- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories
- Bag cutting kit
- Support for liquid packaging
- Additional filling plates

## ACCESSORIES

- Bag cutting kits
- Filling plates
- Liquid insert plates
- Vac-norm external vacuum kits
- Vac-norm containers
- Smooth bags for vacuum packing
- Trolley for vacuum packing machines
- Thermal labels for CG2 / RB printer
- RB Desktop printer for SU vacuum packing machines
- Thermal transfer labels for RB printer

## SPECIFICATIONS

Pump capacity: 20 m<sup>3</sup>/h  
 Pump capacity (60 Hz): 20 m<sup>3</sup>/h  
 Bar length: 420 mm + 420 mm  
 Total loading: -- W  
 Vacuum pressure (maximum): 2 mbar

### Internal dimensions

- ✓ Width: 568 mm
- ✓ Depth: 431 mm
- ✓ Height: 215 mm

### External dimensions (WxDxH)

- ✓ Width: 634 mm
- ✓ Depth: 552 mm
- ✓ Height: 513 mm (230V) / [v:dim\_ext\_alto\_2] (120V)
- ✓ Depth: 552 mm
- ✓ Height: 513 mm

Net weight: 76 Kg

Noise level (1m.): 75 dB(A)  
 Background noise: 32 dB(A)

### Crated dimensions

786 x 612 x 685 mm  
 Gross weight: 84.6 Kg





# VACUUM SEALER SU-520CC

Tabletop model. 20 m<sup>3</sup>/h. 420+420 mm.



## AVAILABLE MODELS

|         |   |
|---------|---|
| 1141100 | SU-520 CC 230/50-60/1                           |
| 1141127 | SU-520GP+ CC 120/60/1                           |
| 1141101 | SU-520G CC 230/50-60/1                          |
| 1141102 | SU-520P CC 230/50-60/1                          |
| 1141103 | SU-520+ CC 230/50-60/1                          |
| 1141104 | SU-520P+ CC 230/50-60/1                         |
| 1141105 | SU-520GP CC 230/50-60/1                         |
| 1141106 | SU-520G+ CC 230/50-60/1                         |
| 1141107 | Vacuum packing machine SU-520GP+ CC 230/50-60/1 |
| 1141120 | SU-520 CC 120/50-60/1                           |
| 1141121 | SU-520G CC 120/50-60/1                          |
| 1141122 | Vacuum packing machine SU-520P CC 120/50-60/1   |
| 1141123 | SU-520+ CC 120/50-60/1                          |
| 1141124 | SU-520P+ CC 120/50-60/1                         |
| 1141125 | SU-520GP CC 120/50-60/1                         |
| 1141126 | SU-520G+ CC 120/50-60/1                         |
| 1141119 | SU-520GP CC 230/50-60/1 AUS                     |

\* Ask for special versions availability

FOOD PRESERVATION AND SOUS-VIDE  
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

 **sammic** | [www.sammic.com](http://www.sammic.com)  
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36  
20720 Azkoitia, Spain [sales@sammic.com](mailto:sales@sammic.com)



|          |      |
|----------|------|
| Project  | Date |
| Item     | Qty  |
| Approved |      |

product sheet  
updated 28/09/2022