

FABRICANTES DE MOLINOS DE CAFÉ

MANUFACTURERS OF COFFEE GRINDERS Molino de café profesional para todo tipo de cafés

Professional coffee grinder for all types of coffee.

ICONIC "45dB"

ABS

COLLECTION SILENCER





GRINDING ONLY 5°

Cuni

0-500gr/5' Max 3Kg TECHNICAL CHARACTERISTICS

VOLTAGE: 230V / 220V / 110V FREQUENCY: 50HZ / 60HZ PHASES: 1(MONOPHASE) RPM: 1.300 / 1.600 CURRENT: 1.5A / 3.5A CAPACITOR: 14µF / 40µF POWER: 0,25HP / 356W PROTECTION RATING: IP21 MOTOR SUPPLIED WITH THERMAL PROTECTOR MAXIMUM OPERATING TIME: 30 MIN.

TEMPERED STEEL GRINDING WHEEL (62HRC) Ø 65MM

LIFESPAN OF GRINDING WHEELS: 500KG

HOPPER CAPACITY: 1KG

DOSER CAPACITY: 600G DOSER REGULATION: 5/12G

DOSER LEVER: RIGHT/LEFT

STOP/START STANDARD VERSION: AUTOMATIC

DIMENSIONS WIDTH X LENGTH X HEIGHT: 210X380X660MM

WEIGHT: 12KG AIR NOISE: 45DB

Diseñado bajo directiva 89/392 CE.








Grinding blades in tempered steel









GREY

WHITE



BI ACK



RED







Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. - Micrometric regulation of the coffee grind using a regulatory pawl. - New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). - Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). –Universal coffee tamper (rotatable) ABS body, two halves specially designed for ventilation and anti-vibration of the body with 7 floating points using pneumatic rings. - Motor set with anti-vibration system and central separator from the motor zone. - Silent 356W motor internally self-ventilated, 45db - Hardened steel grinding blades (62/65 HRc) of 65mm diameter.

Optional: Left or right-handed doser lever. - Coffee counter. - Personalization System with chrome plate on the back of the body and into the funnel. - Admits hopper of 2 kg. Titanium-coated burrs (62/63 HRc) 65mm diameter, 2.000 kg. - Red speed coated burrs (62/63 HRc) 65mm diameter, 3.000 kg.